

Interior Substrates:

- #555A Adhesive** (Field)
- #300 Epoxy Adhesive** (Extreme Use)
- Double Face Tape** (Under Seams)
- Lonsealer - Liquid Seam Sealer**
OR
- Welding Thread**

FACTORY UV-CURED URETHANE MATERIALS:

- Must use Urethane Nozzle for Heat Welding**

Interior Vertical:

- #555A Adhesive** (Field - Roller Apply)
- #400 Contact Adhesive** (Roller Apply)
- Lonsealer Type "C"- Liquid Seam Sealer**
OR
- Welding Thread** (If specified)

Exterior Substrates: (In the Londeck manual)

- #555A Adhesive** (Field)
- #400 Contact Adhesive**
(Use for wrapping pipes, stairs and upholstered edges)
- #300 Epoxy Adhesive**
(At exposed edges of deck and around drains, pipes, etc.,)
- Lonsealer "Type C" – Liquid Seam Sealer** (Stair/vertical installations)
- GeoCel 2300** (use caulk at exposed edges)

Adhesives & Sundries:

- #555A Adhesive:** 3 gal. unit & 1 gal. unit (See Table Above)
- #400 Contact Adhesive:** 1 gal. unit (average coverage - 150 sq. ft./per surface)
Maintain application of adhesive to both surfaces (substrate + vinyl)
- #300 Epoxy Adhesive:** 1 gal. unit (average coverage - 110 sq. ft.)
(Extreme Use – i.e. Commercial Kitchen & Bathrooms)
- Lonsealer- Liquid Seam Sealer:**
1 Tube 4.5 oz (average coverage - 200 lin. ft.)
- Lonsealer "Type C":**
1 Tube 4.5 oz (average coverage - 80 lin. ft.)
- Double Face Tape:** 1 roll (coverage 2" x 60")
- Welding Thread:** 100 ft. min or 1 spool @500 ft.
- Loncare:** 1 gal. unit (average coverage - 2,000 sq. ft./gal)
- Lonbuff:** 1 gal. unit (average coverage - 4,500 sq. ft./gal)
- Lonprime:** 1 gal. unit (average coverage - 3,500 sq. ft./gal)
- Lonfinish:** 1 gal. unit (average coverage - 2,500 sq. ft./gal)
- Lonsatin:** 1 gal. unit (average coverage - 2,500 sq. ft./gal)
- Lonstrip:** 1 gal. unit (average coverage - 2,000 sq. ft./gal)

#555a TROWEL and ROLLER SPREAD RATE SPECIFICATIONS for INTERIOR and EXTERIOR Products

	"V" notch Interior Porous	Fine notch Interior Non-Porous	"Square" notch Exterior - All
Trowel:	1/16" x 1/16" x 1/16"	1/32" x 1/16" x 1/32"	1/16" x 1/16" x 1/16"
*Spread / gal.	180-215	200-260	160-180
**Minutes open time	15-25	10-15	15-25
**Minutes working time	15-25	15-25	15-25
Roller:	Approximately 250-300 sq. ft. per gallon		

*Actual job site coverage may vary according to substrate conditions
**Average minutes at 70°F (21°C).

Maintenance Products:

- Loncare** – neutral pH damp mop floor cleaner
- Lonbuff** – spray buff floor cleaner for glossy UV products
- Lonprime** – floor sealer that increases adhesion of floor finish to Lonseal Flooring (eliminates peeling of floor finish)
- Lonfinish** – high performance glossy floor finish
- Lonsatin** – high performance matte floor finish
- Lonstrip** – no-rinse, highly effective floor finish stripper

GeoCel 2300 – Use caulk at exposed edges.

*Additional information can be obtained within the *Technical Manual for Exterior Products.*

1 - 10.6 fl. oz. Cartridge

Theoretical Yield per Cartridge:

<u>Joint Size</u>	<u>Linear Feet</u>
1/4" x 1/4"	25.5
1/4" x 3/8"	16.9
1/2" x 3/8"	8.4
1/2" x 1/2"	6.4
3/4" x 1/2"	4.2

All orders are required to be faxed to Lonseal's at (888) 566-7325 or emailed to orders@lonseal.com

Revised: 5/27/10

LONSEAL