

## LONFINISH

This high performance metal interlocked high gloss finish with new SPT – Synergistic Polymer Technology, which incorporates the best properties of several polymers in a synergy that is unsurpassed to create a uniquely formulated high gloss finish for resilient sheet vinyl.

### Features and Related Benefits

Finish	Single product with dual product characteristics
Synergistic Polymers	Formulated for durability and “wet look” gloss
User Friendly	Easy to apply, repair and recoat
Premium Quality	Outstanding performance

### Areas of Use

May be used with electric, battery, or propane equipment in: Restaurants, hotels, motels, offices, hospitals, nursing homes, doctors offices, schools, universities, child care centers, grocery stores, malls, retail stores

### To Use –

To achieve the desired “wet-look” we suggest: cleaning the existing non-finished floor with Loncare neutral pH cleaner and allowing drying. Apply 1 thin coat of Lonprime, base seal coat, prior to application of Lonfinish. Apply this product in a uniform, thin coat with a microfiber mop pad/mop. Allow to dry completely (30-45 minutes) between coats. Apply subsequent coats in the same manner. A minimum of two to four coats are recommended for initial application. DO NOT dilute Lonfinish or use on surfaces colder than 45°F.

*Average Coverage:* 2,500 s.f./gallon.

Please refer to *Lonseal’s Technical Manual for Interior Flooring Products* or [www.lonseal.com/maintenance](http://www.lonseal.com/maintenance) for further information.

Specification Data			
Available Sizes - 1G	Physical State - Liquid	Color - White emulsion	Fragrance - Acrylic
Total solids - 18%	Metal Interlocked - Yes	Initial Gloss - Very High	Traffic Area - High
pH - 8.2	Slip Resistance - Exceeds ASTM D 2047	Specific Gravity - 1.022	Burnisher Response - Excellent

Revised: 2/18/09-kh

928 East 238<sup>th</sup> Street | Carson, California 90745 USA  
 Phone: 310.830.7111 | Toll Free (USA only): 800.832.7111  
 Fax: 310.830.9986 | Toll Free (USA only): 888-LONSEAL  
 Email: [info@lonseal.com](mailto:info@lonseal.com) or visit us at [www.lonseal.com](http://www.lonseal.com)