

LONPRIME

An all-purpose base seal coat ideal for use on resilient sheet vinyl as a foundation prior to applying floor finish. Ease maintenance and repair costs with this base seal coat. Reduces excessive scuffing, flaking and peeling of floor finishes.

Features and Related Benefits

High solids	Outstanding cohesion to floor finish
High Performance	Eliminated floor finish peeling and flaking
Water-based	VOC compliant

Areas of Use

May be used with electric, battery, or propane equipment in: Restaurants, hotels, motels, offices, hospitals, nursing homes, doctors offices, schools, universities, child care centers, grocery stores, malls, retail stores

To Use –

Floors should be clean and dry prior to application. A single thin coat, properly applied, will provide an excellent barrier and improve adhesion of floor finish to the surface of resilient sheet vinyl. Apply in a thin coat with a microfiber mop pad/mop and allow to completely dry (30-40 minutes) prior to applying a floor finish.

Average Coverage: 3,500 s.f./gallon.

Please refer to *Lonseal's Technical Manual for Interior Flooring Products* or www.lonseal.com/maintenance for further information.

Specification Data			
Available sizes - 1G	Physical State - Liquid	Color - Milky White	Fragrance - Acrylic
Total solids - 19%	Metal Interlocked - Yes	Initial Gloss - High	Traffic Area - Normal-High
Slip Resistance - Excellent	Burnisher Response – N/A	Specific Gravity - 1.02	pH - 8.4