

LONSATIN

LONSEAL

This high performance, low gloss floor finish, specially formulated to provide excellent durability in a commercial setting. This uniquely formulated satin-like floor finish is to be used on resilient sheet vinyl to reduce excessive soil, scuffing and black marks.

Features and Related Benefits

Finish	Single product with dual product characteristics
Synergistic Polymers	Formulated for durability and “matte” finish
User Friendly	Easy to apply, repair and recoat
Premium Quality	Outstanding performance

Areas of Use

May be used with electric, battery, or propane equipment in: Restaurants, hotels, motels, offices, hospitals, nursing homes, doctors offices, schools, universities, child care centers, grocery stores, malls, retail stores

To Use –

To achieve the desired “matte” look we suggest: cleaning the existing non-finished floor with Loncare neutral pH cleaner and allowing drying. Apply 1 thin coat of Lonprime, base seal coat, prior to application of Lonsatin. Apply this product in a uniform, thin coat with a microfiber mop pad/mop. Allow to dry completely (30-45 minutes) between coats. Apply subsequent coats in the same manner. A minimum of two to four coats are recommended for initial application. DO NOT dilute Lonsatin or use on surfaces colder than 45°F.

Average Coverage: 2,500 s.f./gallon.

Please refer to *Lonseal's Technical Manual for Interior Flooring Products* or www.lonseal.com/maintenance for further information.

Specification Data			
Available Sizes - 1G	Physical State - Liquid	Initial Gloss - Low	Total solids - 15%
Color - White emulsion	Fragrance - Acrylic	Traffic Area - High	Specific Gravity - 1.02
Burnisher Response - Excellent	Metal Interlocked - Yes	Slip Resistance - Exceeds ASTM D 2047	pH - 8.0-8.4

Revised: 2/18/09-kh

928 East 238th Street | Carson, California 90745 USA
Phone: 310.830.7111 | Toll Free (USA only): 800.832.7111
Fax: 310.830.9986 | Toll Free (USA only): 888-LONSEAL
Email: info@lonseal.com or visit us at www.lonseal.com