

# LONSTRIP

Non-ammoniated floor finish stripper specially formulated to quickly and aggressively remove floor finish from the surface of resilient sheet vinyl. A concentrated “re-liquifying” floor finish stripper, designed to work with little to no agitation. This product is a tremendous labor and time saver.

**Features and Related Benefits**

Speed Stripping Action	Requires no agitation
Heavy duty emulsifier	Pleasant to use
No harsh caustics	More user friendly
Water-based	Less slippery than traditional strippers

**Areas of Use**

May be used with electric, battery, or propane equipment in: Restaurants, hotels, motels, offices, hospitals, nursing homes, doctors offices, schools, universities, child care centers, grocery stores, malls, retail stores

**To Use –**

For Mop & Vac Stripping: 1.) Dilute 1:5 cold water (21 oz/gal). For heavy build-ups dilute 1:3 (32oz/gal). 2.) Apply liberally and allow to soak about 5 minutes. Keep area wet by adding stripper solution if necessary. **DO NOT ALLOW SOLUTION TO DRY.** 3.) Pick up dilution with mop or wet-vac. 4.) Rinse well with water. 5.) Allow floor to dry thoroughly before applying floor finish. **See label for complete machine stripping directions and use only as directed.**

*Average Coverage:* 2,000 s.f./gallon.

Please refer to *Lonseal’s Technical Manual for Interior Flooring Products* or [www.lonseal.com/maintenance](http://www.lonseal.com/maintenance) for further information.

Specification Data			
Available Sizes - 1G	Physical State - Liquid	Color - Clear Yellow	Fragrance - Butyl
Ammoniated - No	Viscosity - Thin	Water Based - Yes	Emulsifier - Extra Heavy Duty
Flash Point - Nonflammable	DOT - Corrosive	Specific Gravity - 0.996	pH (Undiluted) - 11.6

Revised: 2/18/09-kh