

MATERIAL SAFETY DATA SHEET

Lonseal #555A Sheet Vinyl Adhesive

SECTION 1: MANUFACTURER IDENTIFICATION

MANUFACTURER'S NAME: SPECIALTY CONSTRUCTION BRANDS,INC.
ADDRESS: 1105 SOUTH FRONTENAC STREET
AURORA, IL 60504

MEDICAL EMERGENCY PHONE: 24 HOURS 1-888-853-1758

DATE REVISED: 4/15/2009

TRANSPORT EMERGENCY PHONE(CHEMTREC): 1-800-424-9300

DATE PRINTED: 4/15/2009

PREPARED BY: L. Manriquez

SECTION 2: HAZARDOUS INGREDIENTS/SARA III INFORMATION

DOES NOT CONTAIN TOXIC CHEMICAL(S) SUBJECT TO THE REPORTING REQUIUREMENTS OF SECTION 313 OF TITLE III AND OF 40 CFR 372. HAZARDOUS INGREDIENTS MUST BE REPORTED WHEN PRESENT AT 1.0% OR GREATER.

SECTION 3: PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING POINT: NA

SPECIFIC GRAVITY (H₂O=1): 1.17

VAPOR DENSITY: NA

EVAPORATION RATE: Slower than ether.

SOLUBILITY IN WATER: Soluble

V.O.C. (VOLATILE ORGANIC COMPOUND): -0 g/l - calculated

APPEARANCE: White liquid

% Solids: 55.5

ODOR: Slight Aromatic

SECTION 4: FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: Non Flammable

METHOD USED: NA

FLAMMABLE LIMITS IN AIR BY VOLUME – LOWER: NA

UPPER: NA

EXTINGUISHING MEDIA: use water spray, foam, dry chemical or carbon dioxide

SPECIAL FIRE FIGHTING PROCEDURES: persons exposed to combustion should wear self contained breathing apparatus and full protective equipment.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Possible build up of preassure in container if heated, cool with water spray.

SECTION 5: REACTIVITY DATA

STABILITY: Stable

CONDITIONS TO AVOID: NA

INCOMPATIBILITY (MATERIALS TO AVOID): Oxidizing agents and caustics

HAZARDOUS DECOMPOSITION OR BYPRODUCTS: Nitrogen containing gasses Carbon Dioxide, Carbon Monoxide

HAZARDOUS POLYMERIZATION: Will not occur

MATERIAL SAFETY DATA SHEET

Lonseal #555A Sheet Vinyl Adhesive

SECTION 6: HEALTH HAZARD DATA

ROUTES OF ENTRY: Inhalation and skin contact are expected to be the primary routes of occupational exposure with this product. This material is not expected to cause adverse effects when good industrial hygiene and safety practices are followed.

HEALTH HAZARDS: None Known

ACUTE EFFECTS OF OVEREXPOSURE: None known to occur

CHRONIC EFFECTS OF OVEREXPOSURE: None known to occur

REGULATED CARCINOGEN STATUS:

Unless noted below, this product does not contain regulated levels of NTP, IARC, ACGIH, or OSHA listed carcinogens.

Vinyl Acetate

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: None known

EMERGENCY AND FIRST AID PROCEDURES:

Eyes – Flush with water for 15 minutes, lifting eyelids occasionally.

Skin – Wash with soap and water.

Ingestion – Do not induce vomiting. CALL PHYSICIAN IMMEDIATELY.

Inhalation – Should inhalation problems occur, move victim to fresh air and aid in breathing if necessary.

IF IRRITATION SHOULD DEVELOP OR PERSIST FROM THE ABOVE EXPOSURES, CALL PHYSICIAN IMMEDIATELY.

SECTION 7: PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Contain spill with inert absorbent, keep from entering sewer, watersheds or water systems. Scrape up excess and place in D.O.T. approved container. Clean with soapy water.

HAZARDOUS SUBSTANCE SUPERFUND: NA

WASTE DISPOSAL METHOD: Dispose of as per local, state and federal regulations for non-hazardous aqueous adhesive waste.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Keep container closed and store in cool dry place.

OTHER PRECAUTIONS: NA

SECTION 8: CONTROL MEASURES

RESPIRATORY PROTECTION: None required under normal conditions of use

VENTILATION: Local exhaust; Use with adequate ventilation. Open doors and windows to create cross ventilation during use and until adhesive dries.

EYE PROTECTION: Safety goggles when handling

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: None required

WORK/HYGENIC PRACTICES: Thorough washing of skin with soap and water before eating or drinking.

MATERIAL SAFETY DATA SHEET

Lonseal #555A Sheet Vinyl Adhesive

SECTION 9: SHIPPING INFORMATION

D.O.T. PROPER SHIPPING NAME: Adhesives

HAZARDOUS SUBSTANCE 49CFR CERCLA: NA

HAZARD CODE: NA

D.O.T. HAZARD CLASS: Not regulated

D.O.T. LABELS REQUIRED: NA

D.O.T. PLACARDS REQUIRED: NA

POISON CONSTITUENT: NA

BILL OF LADING DESCRIPTION: Adhesives

CC NO.: NA

UN/NA CODE: NA

CHEMICAL EMERGENCY: CHEMTREC 24 HOURS: 1-800-424-9300

IATA STATUS: Goods are not regulated by IATA rules and regulations

SECTION 9: OTHER REGULATORY INFORMATION

TSCA INVENTORY STATUS: Listed on Inventory: Yes

PROPOSITION 65:

If your business resides in the state of California or if you supply products directly or indirectly into California, we are providing this information to you pursuant to the California Safe Drinking Water and Toxic Act of 1986 (commonly known as proposition 65). This law requires, in part, that no person in the course of doing business shall knowingly and intentionally expose any individual to chemicals known to the state to cause cancer or reproductive toxicity without first exempt from the warning requirements "an exposure for which the person responsible can show that the exposure poses no significant risk..." (Section 25249.10)

There may be small, perhaps undetectable amounts, of other naturally occurring chemicals that are known to the State of California to cause cancer, birth defects or other reproductive harm. This warning is provided in the absence of definitive testing to prove that these risks do not exist. These amounts are typical quantities and may be below the Proposition 65 level of concern, or could be zero.

OSHA Standard 29CFR 1910.1200 requires that information be provided to employees regarding the hazards of chemicals by means of a hazard communication program including labeling, material safety data sheets, training and access to written records. We request that you and it is your legal duty to, make all information in this material safety data sheet available to your employees.

The Following ingredients are considered to be classified as per OSHA Hazard Communication Standard (29CFR1910.1200):

SECTION 10: DISCLAIMER INFORMATION

***THE CRITERIA FOR LISTING COMPONENTS IN THE HAZARDOUS INGREDIENTS SECTIONS IS AS FOLLOWS: CARCINOGENS ARE LISTED WHEN PRESENT AT 0.1% OR GREATER; COMPONENTS WHICH ARE OTHERWISE HAZARDOUS ACCORDING TO OSHA ARE LISTED WHEN PRESENT AT 1.0% OR GREATER.

While this information and recommendations set forth herein are believed to be accurate as of the date hereof, Specialty Construction Brands, Inc. MAKES NO WARRANTY WITH RESPECT HERETO AND DISCLAIMS ALL LIABILITY FROM RELIANCE THEREON.

The information contained within the MSDS is considered proprietary and is a trade secret. Unauthorized distribution or duplication of this is prohibited.
