

Spray-Lock™ #3500 Resilient Sheet Vinyl adhesive —*alternate adhesive*—

Lonseal and Interlock Industries, Inc. have completed compatibility testing of Spray-Lock™ #3500 Resilient Sheet Vinyl adhesive with all interior Lonseal sheet vinyl flooring products and Spray-Lock™ #3500 Resilient Sheet Vinyl adhesive is approved by Interlock Industries, Inc for Lonseal flooring products.

If specified, for installations incurring heavy static loads such as hospital beds, heavy rolling loads and pallet jacks, etc. then such adhesive would be in lieu of Lonseal's recommended adhesives: #755 Premium Bond, #400 Contact, #300 Epoxy.

DISCLAIMER: Use of the Spray-Lock™ #3500 Resilient Sheet Vinyl adhesive with Lonseal sheet vinyl flooring is subject to Interlock Industries, Inc. limited warranty. This includes support for product performance claims and provisions on warranty coverage. Lonseal does not sell or market Spray-Lock™ products nor is the Spray-Lock™ system covered by Lonseal's warranty.

Spray-Lock™ #3500 Resilient Sheet Vinyl adhesive product benefits:

- Heat weld the same day
- <0.0g/ml VOC
- Immediately allow all traffic (including hospital beds)
- Non-flammable
- 7lb vapor emissions / 85% RH with a pH 11

For additional information and assistance with Spray-Lock™ #3500 Resilient Sheet Vinyl adhesive, please contact Larry Moore of Interlock Industries, Inc. at 479-631-0148 or via email at ldmoore@spraylock.com.