

Begin 48 hours after installation

The floor should always be clean to minimize any slip hazard from build up of dust and tracked-in contaminants. When the floor is properly cleaned, you will notice increased traction.




ALWAYS WEAR GOGGLES, GLOVES AND SLIP RESISTANT SHOES WHEN USING THIS PRODUCT.

Initial and Daily Maintenance


LONSEAL
FLOORCARE

LONCARE

NEUTRAL pH FLOOR CLEANER FOR
RESILIENT SHEET VINYL




1. Install and maintain entry matting with a non-staining backing to reduce tracked-in dirt and contaminants.



2. Sweep with a soft bristle broom or microfiber dust mop the entire area to remove dust and debris.



1. Dilute **LONCARE** 2oz per gallon of cold tap water. Damp mop using a clean microfiber mop pad.



1. To remove scuff marks BUFF area with a low speed machine equipped with a clean contact pad until clean and dry.
2. Change contact pads when they get clogged.

Note: Always use quality pH neutral cleaning products. Harsh cleaning products (i.e. Pine Sol, Mr. Clean) can cause damage to **LONSEAL's** flooring product.


Revitalize Gloss (As Needed)

The length of time required for interim maintenance or revitalizing varies and is dependent upon usage and traffic.


LONSEAL
FLOORCARE

LONBUFF


SPRAY BUFF FLOOR REVITALIZER



1. Sweep with a soft bristle broom or microfiber dust mop the entire area to remove dust and debris.



2. Spray a fine mist of **LONBUFF** over a small area to be cleaned (about 5 feet at a time).



1. Immediately BUFF sprayed area with a low speed machine equipped with a clean contact pad until clean and dry.
2. Change contact pads when they get clogged.
3. Once the surface is clean and completely dry, DRY BUFF with a contact pad on a low speed machine to enhance the luster.

Note: Do not use abrasive pads, brushes or cleaning agents.