



LONNOVA UV

Revolutionizing the iridescent hues of our popular Lonfloor Galvanized series with the addition of a tough 100-micron-thick, factory-applied, UV-cured urethane finish, a breathtaking light-shifting range of 12 colors, and an increased size of metallic-chip patterning, Lonnova UV presents a strong statement with three dimensional depths in its design. The awe-inspiring aesthetics and the ease of maintenance beautifully combine the benefits of form and function.

LONSEAL
FLOORING



Customer Service

For more information on our products and services – including custom-coloring, pricing, and order placement – please give us a call at: **800 832 7111**

Order Samples

To request free samples & other information online, visit our website at: **www.lonseal.com** or call: **800 832 7111**

LONNOVA UV

Thickness 80 mil (2.0 mm)
Standard Width 6 feet (1830 mm)
Roll Length 60 feet (18m)

Available in 12 stunning colorways.

Product Name

LonNova commercial grade sheet vinyl flooring.

Lonseal, Inc.

928 E. 238th St., Carson, CA 90745
Phone: (800) 830 7111, Fax: (310) 952 7651
www.lonseal.com

Product Description

LonNova provides a low maintenance layer of UV cured urethane fused to a PVC matrix to create an eco-friendly environment, outstanding durability and ease of maintenance. The exotic color palette provides excellent camouflage for scuffing and soil.

Applications: Excellent for interior retail, commercial or institutional use.

Limitations: Not for outdoor use. May show temporary indentations from heavy point loads, i.e. hospital beds.

Suitable Substrates: Subject to the Lonseal Technical Manual for Interior Products (online version) – Concrete (all grade levels), underlayment grade plywood, metal, terrazzo, fiberglass and existing single layer resilient flooring.

Composition: Heterogeneous resilient sheet vinyl composed of polyvinyl chloride (PVC) resin, plasticizer, pigment, and fillers with factory applied 100 micron thick, clear, UV cured, urethane applied to the surface.

Beneath the high-gloss UV cured top layer, the PVC wear layers provide dazzling coloration and durability.

Together, they provide maximum resistance to foot traffic and most chemicals common to commercial and healthcare settings.

The middle layer provides dimensional stability, sound absorbing properties, and under foot resiliency.

The backing material provides strength and stability of the flooring and enhances the bonding strength of the adhesive.

Easy Maintenance and Great Stain Resistance.

LonNova UV's urethane finish can banish wet-mopping detergent or cleaning chemicals from your cleaning routine. Its twice as strong wear-layer UV finish actually allows your maintenance crew to erase the dirt with wet or dry micro fiber mopping as easily as wiping a whiteboard clean.

Weight: .7 lb./sq. ft., 247 lb./Roll

Colors: 12 Available

VAPOR 260	HEAVENLY 262	ATMOSPHERE 264	GOLDENGLow 266	TWINKLE 268	BLAZING STAR 270
SUNBEAM 272	SATELLITE 273	MOONLIGHT 275	COSMOS 276	DAYBREAK 277	SKY 279

LONSEAL

FLOORING