## LONSEAL® **FLOORING**

## **LONFLOOR® GALVANIZED Topseal**

Industrial Pearlescent with Clean Lines

LONFLOOR GALVANIZED with Topseal lends a striking industrial touch to any interior, from office break rooms to retail spaces. The subtle color choices offer warmth while the metallic design gives a polished, sophisticated appeal. Lonseal's exclusive Topseal formulation is a factory-applied urethane finish that protects the floor, reduces scuffing and simplifies routine maintenance.

FEATURES (data shown is nominal):

Roll Width: 6 ft. (1.8 m) Roll Length: 60 ft. (18.3 m)

Overall Thickness: 0.080 in. (2.0 mm) Wear Layer Thickness: 0.032 in. (0.8 mm)

Weight: 0.6 lbs./sq. ft. (3.0 kg/m<sup>2</sup>)

ASTM F1303 CLASSIFICATION: Type I, Grade 1, Class B, Commercial Use

CERTIFIED:

FloorScore®

**EXCLUSIVE LONSEAL FORMULATIONS:** Topseal, GreenAir® & GreenMedic®

LEEDv4/4.1 CONTRIBUTION B & C Interiors:

**Environmental Product Declarations Option 1** 

Sourcing of Raw Materials Option 2

Low-Emitting Materials

Pre-Consumer (Post-Industrial) Recycled Content

procedures are necessary to ensure a long-lasting installation. In addition, areas of prolonged UV exposure should be avoided to prevent unwanted discoloration of the flooring.

\* Due to the light color of #F7240 White Diamond, more frequent maintenance ▲ WARNING: Cancer and Reproductive Harmwww.P65Warnings.ca.gov



