

LONDECK is a resilient, slip-resistant exterior sheet vinyl with an embossed surface that withstands high volumes of pedestrian traffic and weather wear. It has been utilized around pools, on hotel and condo decks, and on rooftops and stairways. Though designed for exterior spaces, the Londeck line is equally appropriate for interiors.

STANDARD SIZES (nominal)

Overall thickness: 0.080" (2.0 mm)

Wear layer thickness: 0.031" (0.8 mm)

Roll Size: 6' (1.830 m) wide x 60' (18.3 m)

Weight: .7 lb/sq. ft., 245 lbs/roll/

Colors: Eight available

15-YEAR WARRANTY

Lonseal offers a 15-year limited warranty.

TECHNICAL DATA

Weatherometer ASTM D1499	No crazing, cracking, spalling or softening
Accelerated Aging, ASTM D756	43psi
Fire Retardant Roof Covering, ASTM E108	Class "A" Concrete Class "B" ¾" Plywood
Tensile and Elongation (≤55%), ASTM D751	Weathered 9% Aged 20%
Bond Strength (10psi. Min.), ASTM C297	Control 30psi. Aged 43psi. Freeze Thaw 22psi.
Abrasion (max 0.020"), ASTM D1242	0.001"
Percolation (0.5" Max), AC 39	0.1"
Water Absorption (15% Max), ASTM D570	5%
Chemical Resistance, ASTM D2299	No crazing, cracking, spalling or softening
Freeze Thaw (15% Max), ASTM C67	1%
Concentrated Load, AC39	No damage noted
Wind Uplift, FM 1-52	No cracking, spalling, tearing, delamination or failures of fasteners

For detailed installation information, please refer to Lonseal's Technical Manual for Interior Flooring Products at www.lonseal.com.

LONSEAL, INC.
928 E. 238th Street, Carson, CA 90745 USA
800.832.7111 toll free | 310.830.7111 ph
www.lonseal.com



Updated: 2/08/11